Warwick Range



WBN3112 Wash Bowl

Long Life Re-usable Polypropylene Wash Bowl for use in Decontamination Services, Hospitals, Clinics and Nursing Homes



The Warwick Range of polypropylene products from Warwick SASCo was originally designed to offer an alternative to stainless steel products traditionally used in Hospitals.

This Range is now widely used in Decontamination Services, Operating Rooms and Clinics due to its low cost, effective product design, and performance in hospital autoclaves.

Easily recognised by its distinct blue colour, the Warwick Range includes bowls, gallipots, kidney dishes, instrument trays, instrument protection, instrument boxes, traceability tags, measuring jugs, scope and instrument soaking containers.



Warwick House, Heathcote Way, Warwick, CV34 6TE

T: +00 44 (0)1926 422427 F: +00 44 (0) 1926 315405

E: info@sasco.co.uk W: www.sasco.co.uk

Product Benefits

- Lightweight, strong and durable 50% lighter than stainless steel
- Improved removal of blood residue compared to stainless steel
- Grip feature moulded below the rim to improve holding
- Can be sterilized by Autoclave, Ethylene Oxide or Hydrogen Plasma
- Smooth edges and surfaces eliminate paper rips during sterilization and packing
- Smooth rim ensures no dripping when pouring liquids

Product Specification

- 3000ml Wash Bowl
- 310mm x 105mm
- Pack Size 25
- The following standards are applicable:
 - ISO 9001:2008
 - Design, manufacture and distribution of plastic medical devices for hospitals and home care
 - ISO 13485:2003
 - Design, manufacture and distribution of plastic medical devices for hospitals and home care
 - BS EN 980:2008
 - Symbols for use in Labelling of Medical Devices
 - BS EN 14971:2007
 - Application of Risk Management to Medical Devices
- Manufactured from virgin grade polypropylene
- Autoclavable up to 135 ° C

Guide to Using Warwick Products from Warwick SASCo

- Product should be washed before first use.
- Warwick Products are designed for a lengthy service guaranteed for 1000 washes and sterilizations. Scouring and abrasive cleaners will reduce the performance of products.
- Product should be processed complying with requirements of ISO17664.
- This product has a shelf life of 36 months from date of manufacture providing the recommended storage conditions are adhered to.
- Product should be stored in its primary packaging, off the floor on a pallet or shelf, and in a clean dry ventilated room at a temperature of 4 °C - 25 °C.